

DYNAMIC 620 START







- Battery charger and starter for 12/24V WET batteries and rapid cranking of all types of cars, vans, light goods vehicles. 570A max.
- Normal charge, fast (BOOST) charge, rapid cranking selection.
- Display of charging and cranking current.







TECHNICAL DATA

CODE	829384	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPA	AC. 20 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFECTIVE CHARGING CURRENT	90 A	MAX.RATED REFERENCE CAP	AC. 1550 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	70 A	ADJUSTMENT POSITIONS	4
CHARGING ABSORBED POWER	2 kW	START CUR.1V/C EN60335-2-29	360 A	DIMENSIONS (LxWxH)	36,5 x 46 x 75,5 cm
STARTING ABSORBED POWER	10 kW	MAX STARTING CURRENT	570 A	WEIGHT	24 kg

OPTIONAL ACCESSORIES

BATTERY CHARGERS FUSES

802029 FUSES 100A 20 PCS

DESCRIPTION

Battery charger and starter for charging free electrolyte batteries (WET) with 12V/24V voltage and starting all kinds of cars, vans and light trucks.

Features:

- choice of normal charge, quick charge (BOOST), quick start;
- timer for quick charge;
- display of charging and starting current;
- protection against overloads and polarity reversal.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST